

6.3 ARC LENGTH (CONTINUED)

Recall, the arc length formula:

$$L = \int_a^b \sqrt{dx^2 + dy^2}. \quad (1)$$

This can be parametrized in many ways, but there are two main ways:

$$L = \int_a^b \sqrt{1 + f'(x)^2} dx \quad \text{if } f \in C^1([a, b]), \quad (2)$$

$$L = \int_c^d \sqrt{1 + g'(y)^2} dy \quad \text{if } g \in C^1([c, d]). \quad (3)$$

- (1) Set up the integral for the arc length of $y = \sqrt{x}$ from $(0, 0)$ to $(1, 1)$.

Solution: Since this won't work for y as a function of x , we need x as a function of y : $x = y^2$. Then, $dx/dy = 2y \Rightarrow L = \int_0^1 \sqrt{1 + 4y^2} dy$.

- (2) Set up the integral for the arc length of $x = \int_0^y \sqrt{\sec^2 t - 1} dt$ from $y = -\pi/3$ to $y = \pi/4$.

Solution: We differentiate, $dx/dy = \sqrt{\sec^2 y - 1}$. Then plugging into our formula gives, $L = \int_{-\pi/3}^{\pi/4} \sec y dy$.

- (3) Set up the integral for $y = \ln x$ from $(1, 0)$ to $(e, 1)$.

Solution: Again, we differentiate, $dx/dy = 1/x$. Then we plug it into our formula to get, $L = \int_1^e \sqrt{1 + 1/x^2} dx$

6.4 AREAS OF REVOLUTION

Areas of revolution are similar to volumes of revolution, except now, we integrate over the length of the arc, so for a revolution about the x-axis we have

$$SA = 2\pi \int_a^b f(x) \sqrt{1 + f'(x)^2} dx \quad (4)$$

And similarly for a revolution about the y-axis we have

$$SA = 2\pi \int_c^d g(y) \sqrt{1 + g'(y)^2} dy \quad (5)$$

However, just like for arc lengths, we can parametrize this in many different ways, but one convenient way to do it is as such:

$$\begin{aligned} \text{SA} &= 2\pi \int_c^d y \sqrt{1 + g'(y)^2} \, dy \\ \text{SA} &= 2\pi \int_a^b x \sqrt{1 + f'(x)^2} \, dx. \end{aligned}$$

But, do not concern yourselves too much with these formulas, but it is important to realize there are many different ways we can solve the same problem.

- (1) Find the surface area of $y = \sqrt{4 - x^2}$ bounded by $-1 \leq x \leq 1$ revolved about the x -axis.

Solution: We first differentiate to get $\frac{dy}{dx} = \frac{-x}{\sqrt{4-x^2}}$. Then we simply plug into the formula to get,

$$\text{SA} = 2\pi \int_{-1}^1 \sqrt{4-x^2} \sqrt{1 + \frac{x^2}{4-x^2}} \, dx = 2\pi \int_{-1}^1 \sqrt{4-x^2 + (4-x^2) \frac{x^2}{4-x^2}} \, dx = 2\pi \int_{-1}^1 2 \, dx = 8\pi.$$

- (2) Find the surface area of the curve $y = x^2$ from $(1, 1)$ to $(2, 4)$ revolved about the y -axis.

Solution: Differentiating gives $\frac{dx}{dy} = \frac{1}{2\sqrt{y}}$, then plugging into the formula gives

$$\text{SA} = 2\pi \int_1^4 \sqrt{y} \sqrt{1 + \frac{1}{4y}} \, dy = 2\pi \int_1^4 \sqrt{y + \frac{1}{4}} \, dy.$$

This is solved via u-sub, where $u = y + \frac{1}{4}$, which gives

$$\text{SA} = 2\pi \int_{5/4}^{17/4} \sqrt{u} \, du = \frac{\pi}{6} (17\sqrt{17} - 5\sqrt{5}).$$

6.5 WORK

Work is the sum of forces exerted over a certain distance. It's induced by an action. For a constant force, it will be $W = Fd$, where W is the work, F is the force or equivalently the weight, and d is the distance traversed.

- (1) How much work does it take to lift a 1.2-kg book .7m?

Solution: Assuming $g = 9.8$, the force is $F = mg = (1.2)(9.8)$, then the work is $W = Fd = (1.2)(9.8)(.7)$ J.

- (2) How much work does it take to lift a 6-lb weight 6ft?

Solution: Here we are already given the weight, which is equivalent to force, so $W = Fd = (6)(6) = 36$ ft-lb.

Now, what if the force changes as a function? Then we need to add up all parts of the force, so we get the equation: $W = \int_a^b F(x)dx$.

- (3) Suppose the force is given by the function $f(x) = x^2 + 2x$ -lb, where x is the distance the object is being moved. Find the work done to move this object from $x = 1$ ft to $x = 3$ ft.

Solution: We simply plug this into the formula for work to get $W = \int_1^3 (x^2 + 2x)dx = \frac{1}{3}x^3 + x^2 \Big|_1^3 = \frac{50}{3}$.

- (4) Consider a mass on a spring. It takes 40N to stretch it from it's natural length of 10cm to a length of 15cm. Find the work to stretch it from 15cm to 18cm.

Solution: We recall Hooke's law states that a mass on a spring feels a force proportional to the length the mass is stretched from the spring's natural position (i.e. $F = kx$), where x is the distance from the natural position and k is the spring constant.

Notice the natural length is at 10cm and the length that it is stretched to is 15cm, so lets denote the natural length as x_* and the initial stretched length as x_0 , then $x_* = 0$ because the natural length is always defined to be at $x = 0$ and $x_0 = 5$ cm because it is 5cm away from the natural length.

Also notice, the units are in cm, so we must change them to the proper SI units of meters: $x_0 = 5$ cm = .05m (the initial length) and $x_1 = 8$ cm = .08m (the length we want to stretch it to). First, we need to back out the spring constant,

$$f(x_0) = kx_0 = k(.05) = 40 \Rightarrow k = 800 \Rightarrow F(x) = 800x.$$

Now, we just plug this into the formula for work to get,

$$W = \int_{.05}^{.08} 800x dx = 400x^2 \Big|_{.05}^{.08} = 1.56\text{J}.$$

Tougher examples.

We may not always have a problem where we can put quantities into a set formula. Many times we'll have to derive our own formula. These are the sort of problems they love to put on exams.

- (1) Consider a 200lb - 100ft long cable hanging off the top of a building. Find the work it takes to pull the entire cable to the top of the building.

Solution: Lets define our coordinate system to be 0 at the top and 100 at the bottom. Now, lets break the cable up into i pieces, such that the i^{th} piece is at a distance x_i from the top and has a length of Δx_i . Notice the cable is 2lbs per ft, so the i^{th} cable weighs $F = 2\Delta x_i$. Then, the work it takes to move the i^{th} piece to the top is $W_i \approx 2x_i\Delta x_i$. Now we sum these pieces up and take the limit as $\Delta x_i \rightarrow 0$ in order to get the exact work done. This gives us an integral,

$$W = \int_0^{100} 2x dx = x^2 \Big|_0^{100} = 10^4 \text{ ft-lb.}$$

- (2) Consider a conical tank where the base is on top and the point is on the bottom. It has a radius of $r = 4\text{m}$ and a height of 10m. Suppose the tank is filled to 8m from the bottom with water. Assuming water has a density of $\rho = 1000 \text{ kg/m}^3$, find the work it takes to pump all the water out of the tank from the top.

Solution: Lets define our coordinate system to be 0 at the top and 10 at the bottom, so our water level is at $x = 2$. We break the tank up into circular cylinders, such that the i^{th} cylinder has a height of Δx_i and a radius of r_i . We need to find r_i in terms of x_i . We can do this by using similar triangles, i.e. the ratio of the radii will be equivalent to the ratio of the heights of the big triangle (half the cross-section of the tank) and the small triangle (half the cross-section of the water). The ratio is:

$$\frac{r_i}{4} = \frac{10 - x_i}{10} \Rightarrow r_i = \frac{2}{5}(10 - x_i).$$

Now we know the volume of the i^{th} cylinder will be,

$$V_i \approx \pi r_i^2 \Delta x_i = \frac{4\pi}{25}(10 - x_i)^2 \Delta x_i.$$

Then, this has a mass of

$$M_i \approx \rho V_i \approx 1000 \frac{4\pi}{25}(10 - x_i)^2 \Delta x_i = 160\pi(10 - x_i)^2 \Delta x_i.$$

From this we get the weight,

$$F_i \approx M_i g \approx (9.8)160\pi(10 - x_i)^2 \Delta x_i \approx 1570\pi(10 - x_i)^2 \Delta x_i.$$

From this we get the work done to move the i^{th} cylinder to the top,

$$W_i \approx F_i x_i \approx 1570\pi x_i (10 - x_i)^2 \Delta x_i.$$

Taking the limit gives us the near-exact value of,

$$W \approx \int_2^1 01570\pi x_i (10 - x_i)^2 \Delta x_i \approx 3.4 \times 10^6 \text{ J}$$